


High Flux



MBR – MEMBRANE BIOREACTOR FLAT SHEET MEMBRANE HYPER™ PVDF FMBR-E100



Overview

MEGAVISION FMBR PVDF Series, is a high-flux Flat Sheet MBR membrane delivering excellent permeability, fouling resistance, stability and elimination effectiveness.

Structured with Hyper™ PVDF (permanently hydrophilic polyvinyl difluoride) has **the advantage of dry storage**.

FMBR PVDF Series membranes can be used for a wide variety of treatment applications such as industrial and domestic wastewaters.

- Permanently hydrophilic
- High flux & low fouling
- High MLSS concentration
- High chlorine resistance

Product Specifications

Effective membrane area	m ²	1.0
Dimensions (w×h×d)	mm	610x930x12
Weight	Kg	1.2
Nominal pore size	μm	0.2
Membrane material	-	Hyper™ PVDF
Reinforcement frame	-	ABS

Product Performances

Storage & Maintenance	-	Dry Storage
Design flux rate	L/m ² .h	15~30
MLSS	mg/L	4,000~15,000

Operating Specifications

Operating temperature	°C	5~40
DO concentration	mg/L	>1
pH range	-	2~11
Aeration rate	L/m ² .h	≥10
Operating pressure	MPa	-0.02~0
Max. operating pressure	MPa	0.035
Max. pressure drop	MPa	0.03



The information and data contained herein are deemed to be accurate and reliable and are offered in good faith, but without guarantee of performance. MegaVision membrane assumes no liability for results obtained or damages incurred through the application of the information contained herein. Customer is responsible for determining whether the products and information presented herein are appropriate for the customer's use and for ensuring that customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Specifications subject to change without notice. MegaVision Membrane is registered brand of Shanghai MegaVision Membrane Technology & Engineering Co. Ltd. All rights reserved © 2019.